

	<b>Meridian Fire Department</b>	<b>JPR#</b>	<b>P6</b>
	Driver/Operator Performance Standards	Revision Date: 5/30/2024	Standard: NFPA 1002-17: 5.2.4

<b>Description:</b>	Supplying a 2 ½" to 1 ¾" reducing horizontal standpipe		
<b>Conditions:</b>	<p>Given an appropriately equipped fire department pumper apparatus, fire hydrant, objective, Officer and FF, position the apparatus to support the deployment of a 2 ½" to 1 ¾" reduced horizontal standpipe for fire attack.</p> <p>*Driver/Operator may use either a calculator or pump chart for reference during evolution.</p>		
<b>Time Standard:</b>	N/A	<b>Time Adjustments:</b>	N/A
<b>Time:</b>			

Competencies:	Pass	Fail
1. Acknowledges order from Officer		
2. Spots apparatus as directed (Allowing for efficient hose deployment, building collapse zones, structure access, traffic hazards and placement of other key apparatus).		
3. Sets the parking brake		
4. Ensures transmission is in neutral		
5. Ensures motor is at idle		
6. Safely engages pump (Confirms engagement using speedometer and indicator lights)		
7. Exits cab		
8. Sets wheel chocks		
9. Opens <b>TANK TO PUMP</b> valve (Considers/opens recirculation valve).		
10. Confirms hose bed is clear (as appropriate) necessary connections are made and that FF is ready for water.		
11. Opens appropriate discharge valve.		
12. Switches to <u>Pressure Control Mode</u> to provide pressure control protection.		
13. Adjusts throttle to develop and maintain desired pressure for fire stream(s).		
14. Establishes continuous water supply as per JPR-P1/P1a		
15. Makes transition to continuous (hydrant) supply		
16. Closes <b>TANK TO PUMP</b> and refills tank during evolution. Tracks static and residual pressures appropriately		
<b>Application of Hydraulics</b>		
17. Pumps line at proper pressure		

Driver/Operator	Date:
Evaluator	Date: